Serial No. 10/736,650
Docket No. SUPERCON 23
Amendment B UNDER RULE 116
and Telephone Interview Summary

AMENDMENTS TO THE CLAIMS:

REGEIVED CENTRAL FAX CENTER

Kindly amend claim 1 as shown below.

JUL 2 0 2006

This listing of claims will replace all prior versions and listings of claims in the Application:

Claim 1 (currently amended): A process for making superconducting material useful for forming electrolytic devices comprising the steps of:

- a) establishing multiple niobium or tantalum components in a primary billet of a ductile material;
- b) working the primary billet to a series of reduction steps to form said niobium or tantalum components into elongated elements;
- c) cutting the elongated elements from step b) and forming the cut elements into a stack around a metal core;
- d) surrounding the stack of cut and stacked elements from step c) with a porous confining layer to form a secondary billet;
- e) working the secondary billet from step d) through a series of reduction steps[[;]] including twisting and rolling into thin ribbon with an Aspect Ratio of greater than 5:1;
 - f) cutting the worked billet from step e) into sections; and
 - g) leaching the core and sheath at least in part.

Claim 2 (original): The process of claim 1, wherein said leaching is in an acid leach.

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643

175 CANAL STREET MANCHESTER, NH 03101 TEL: 503.668.1400 FAX: 603.668.8557

Serial No. 10/736,650
Docket No. SUPERCON 23
Amendment B UNDER RULE 116
and Telephone Interview Summary

Claim 3 (original): The process of claim 1, wherein said leaching step is in a liquid metal bath.

Claim 4 (original): The process of claim 3, wherein said liquid metal bath comprises molten magnesium.

Claim 5 (previously presented): The process of claim 1, wherein said porous confining layer contains a gap that renders the confining layer circumferentially discontinuous, but overlapping.

Claim 6 (previously presented): The process of claim 1, wherein said porous confining layer contains a gap that renders the confining layer circumferentially discontinuous.

Claim 7 (original): The process of claim 1, wherein several separate segments are used to construct a multi anode capacitor assembly.

Claim 8 (original): An electronic device made from the superconductor material formed by the process of claim 1.

Claim 9 (original): An electrolytic capacitor made from the superconductor material formed by the process of claim 1.

Claim 10 (previously presented): The process of claim 1, wherein said metal core consists of a single metal rod.

Claim 11 (previously presented): The process of claim 10, wherein said single metal rod has a cross-sectional area not exceeding 20% of said secondary billet before working.

HAYES SOLOWAY P.C. 3450 E. SUNRISE DRIVE SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643

175 CANAL STREET MANCHESTER, NH 03101 TEL. 603.668.1400 FAX. 603.668.8567

P.06/11

Serial No. 10/736,650
Docket No. SUPERCON 23
Amendment B UNDER RULE 116
and Telephone Interview Summary

Claim 12 (previously presented): The process of claim 1, wherein the Aspect Ratio is 40:1.

HAYES SOLOWAY P.C. 3450 E. SURRISE DRIVE SUITE 140 TUCSON, AZ 85718 TEL. 520.882.7623 FAX. 520.882.7643

175 CANAL STREET MANCHESTER, NH 03101 TEL. 603.668.1400 FAX. 603.668.8567